



BEARING SUDAMERICANA, S.A.



SKF NSK NTN Timken Koyo NACHI Deep Groove Ball Bearing 6021 607 618/5 61907 6216 6236 63/22 6311 6316 6318 6319 6321 633313 640 6405 6409 6413 6505 Zz RS C3

Bearing No. 6021

6021 Bearing 2D drawings and 3D CAD models

Size	105x160x26 mm
Bore Diameter	105 mm
Outer Diameter	160 mm
Width	26 mm
d	105 mm
D	160 mm
B	26 mm
C	26 mm
r min.	2 mm
da min.	113 mm
Da max.	152 mm
ra max.	2.0 mm
Weight	1.60 Kg
Basic dynamic load rating (C)	72,5 kN
Basic static load rating (C0)	65,5 kN
(Grease) Lubrication Speed	4000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open



BEARING SUDAMERICANA,S.A.

Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	105MM Bore; 160MM Outside Diameter; 26MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nachiamerica.com
Outer Race Width	1.024 Inch 26 Millimeter
Outside Diameter	6.299 Inch 160 Millimeter
Bore	4.134 Inch 105 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	105 mm
Width	26 mm
Fillet Radius/Chamfer	2 mm



BEARING SUDAMERICANA, S.A.

Dynamic Load Rating	72,500 N
Static Load Rating	65,500 N
Limiting Speed - Grease	4,000 rpm
Limiting Speed - Oil	4,800 rpm
Factor f_0	15.8
Radial Clearance	0.015 to 0.041 mm
da (min)	113 mm
Da (max)	152 mm
ra (max)	2 mm